

ClearView Venue Player Comparisons

General Product Configurations

ClearView Venue Players						
Base Models	CVVP-1044	CVVP-2044	CVVP-1084	CVVP-3088	CVVP-1084-DP	CVVP-3084-DP
Form Factor	1 RU, 13.5" deep	2 RU, 13.75" deep	1 RU, 21.5" deep	3 RU, 31.5" deep	1 RU, 21.5" deep	3 RU, 20.2" deep
Video Outputs	4 X SDI-3G	4X SDI-3G	8 X SDI-3G	16 X SDI-3G	4 X Display Port	4 X Display Port
YCrCb 4:2:2 Out Combinations	1x4K, 4x2K	1x4K, 4x2K	2x4K, 8x2K, 1x4K+4x2K	1x8K, 4x4K, 16x2K	NA	NA
RGB 4:4:4 Out Combinations	2x2K	2x2K	4x2K	8x2K	4x2K or 1x4K**	Up to 3x4K**
Max Frame Rate	60	60	60	60	60	60
Bit Depth	10	10	10	10	10	10
Storage Amount	2.5 TB*	2.5 TB*	4 TB*	8 TB*	4 TB*	1.6 TB*
Storage Type	5 SATA SSDs	5 SATA SSDs	8 SAS SSDs	32 SAS SSDs	8 SAS SSDs	4 SSD PCIe Cards
Fan Speed Monitoring	YES	YES	YES	YES	YES	YES
Temperature Monitoring	YES	YES	YES	YES	YES	YES
GNIC	2	2	2	2	2	2
Genlock Input	YES	YES	YES	YES	NO	YES
LTC Input	YES	YES	YES	YES	NO	NO
GPI Input	NO	NO	YES	YES	YES	YES
Nvidia Sync	NO	NO	NO	NO	NO	YES
Warp/Blend	NO	NO	NO	NO	Optional	Optional

*Higher storage capacities are available. **2K in DP models include 1200 line formats.