

General Product Configurations

Venue Players (SDI and DP)						
Base Models	CVVP-2044	CVVP-1084	CVVP-3085-4K	CVVP-3085-8K	CVVP-1084-DP	CVVP-3084-DP
Form Factor	2 RU, 13.75" deep	1 RU, 21.5" deep	3 RU, 31.5" deep	3 RU, 31.5" deep	1 RU, 21.5" deep	3 RU, 20.2" deep
Video Outputs	4 X 12G-SDI	8 X 3G-SDI	4 X 12G-SDI	4 X 12G-SDI	4 X Display Port	4 X Display Port
YCrCb 4:2:2 Out Combinations	1x4K, 4x2K	2x4K, 8x2K, 1x4K+4x2K	2x4K, 4x2K, 1x4K+3x2K	1x8K, 4x4K, 4x2K	NA	NA
RGB 4:4:4 Out Combinations	2x2K	4x2K	1x4K, 4x2K	2x4K, 4x2K	4x2K or 1x4K**	Up to 3x4K**
Max Frame Rate	60	60	60	60	60	120 (with 1x4K)
Bit Depth	10	10	10	10	10	10
Storage Amount	2.5 TB, 5 TB*	4TB, 8TB, 16TB	8TB, 16TB, 32TB	12TB, 24TB*	4 TB, 8 TB, 16TB	6 TB*
Storage Type	5 SATA SSDs	8 SAS SSDs	16 SAS SSDs	24 SAS SSDs	8 SAS SSDs	24 SAS SSDs
Fan Speed Monitoring	YES	YES	YES	YES	YES	YES
Temperature Monitoring	YES	YES	YES	YES	YES	YES
GNIC, 10G NIC	2, 0	2, 0	1, 1	1, 1	2, 0	1, 1
Genlock Input	YES	YES	YES	YES	NO	NO
LTC Input	YES	YES	YES	YES	NO	NO
GPI Input	NO	YES	YES	YES	YES	YES
Nvidia Sync	NO	NO	NO	NO	NO	YES
Warp/Blend	NO	NO	NO	NO	Optional	Optional

*Higher storage capacities are available. **2K in DP models include 1200 line formats.